

ND-R194 165

OPTIMAL DESIGN OF FIBERED STRUCTURES(U) MASSACHUSETTS  
INST OF TECH CAMBRIDGE G STRAWN FEB 88 ARO-19374.9-MA  
DAAG29-83-K-0025


1/1

UNCLASSIFIED

FFG 11/4

NL





MICROCOPY RESOLUTION TEST CHART

IRAL STANDARDS INC.

AD-A194 165 011C FILE COPY

ARO 19374.9-MA

(2)

Optimal Design of Fibered Structures

Final Technical Report

Gilbert Strang  
February 1988

U. S. Army Research Office

Contract DAAG29-83-K-0025

Massachusetts Institute of Technology

Approved for Public Release: Distribution Unlimited

**UNCLASSIFIED**

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER  Final Report 1	2 GOVT ACCESSION NO.	3 RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle)  OPTIMAL DESIGN OF FIBERED STRUCTURES		5. TYPE OF REPORT & PERIOD COVERED  1 Jan 83 - 31 Dec 87 Final Technical Report
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s)  Gilbert Strang		8. CONTRACT OR GRANT NUMBER(s)  DAAG29-83-K-0025
9. PERFORMING ORGANIZATION NAME AND ADDRESS  Massachusetts Institute of Technology Cambridge, MA 02139		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS  U. S. Army Research Office Post Office Box 12211 Research Triangle Park, NC 27709		12. REPORT DATE  February 1988
14. MONITORING AGENCY NAME & ADDRESS(if different from Controlling Office)		13. NUMBER OF PAGES  6
		15. SECURITY CLASS. (of this report)  Unclassified
		16. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)  Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)  NA		
18. SUPPLEMENTARY NOTES  The view, opinions, and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other documentation.		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)  Optimal design, minimum weight, calculus of variations, homogenization, composite materials		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number)  (contained on separate page)		

## Optimal Design of Fibered Structures

### ABSTRACT

The problem of shape optimization is to minimize the area that must be filled by expensive material in order to satisfy design constraints. Those constraints require the structure to withstand a given external load (or family of loads) without exceeding a permissible deformation, or a permissible compliance, or the yield limit of a plastic material.

The design problem is mathematically subtle, because the underlying optimization problem is not convex. Structural equilibrium is governed by a partial differential equation of the form  $\text{div}(c(x)\text{grad } u) = f$ , but in contrast to the analysis problem (which solves for  $u$ ), the design problem is to choose  $c$ . The control variable is the coefficient, and frequently a conventional solution does not exist. The minimum weight design is approached by coefficients  $c$  which jump more and more frequently between alternative states. The design develops a complicated microstructure, and the challenge is to see within that structure a simple and computable pattern.

The limit is a composite material, in which the original materials have well-defined densities and orientations. The composite is achieved by homogenization of the original materials. Mathematically this is expressed by a relaxation, or convexification, of the original minimization problem. The project has seen a successful integration of these fundamental theories (previously developed along separate lines), and the explicit computation of optimal designs in a series of significant engineering problems. ↵

Information For	
IS Critical	
IS ESDU	
IS MILSPEC	
IS Qualifications	
IS Certification	
IS Acceptability Codes	
IS Civil and/or	
Not	Special
IS Copy Inserted	

A-1

Problem and Results: Technical Report

Contract DAAG29-83-K-0025

Optimal Design of Fibered Structures

Professor Gilbert Strang  
Department of Mathematics  
Massachusetts Institute of Technology

The classical variational problems involve the minimization of convex energies subject to boundary conditions. They lead to elliptic differential equations and the solutions are smooth functions away from singularities in the data or the domain. A typical equation is  $\operatorname{div}(c(x) \operatorname{grad} u) = f$ , with a coefficient  $c$  that reflects the material properties.

In contrast, the problem of optimal design is to choose that coefficient  $c$ . The cost function may still be quadratic in  $u$ , or in plasticity problems it may involve the  $L^\infty$  norm of  $c \operatorname{grad} u$ , but the choice between different materials or different shapes is determined by the unknown function  $c$ : it is a problem in which the coefficient is the control variable. In such problems it is common to find that a conventional solution does not exist. The minimum cost is approached by a sequence  $c_n$  that is more and more oscillatory. That corresponds to a series of designs in which materials are combined with an increasingly complicated microstructure.

Mathematically the underlying difficulty is that the variational problem is not convex. In optimal design the cost may be zero in the absence of material and jump to unity whenever the stress is nonzero and material is required. The minimizing sequence of coefficients makes that jump more and more frequently, and there is no convergence in norm to a limit  $c_\infty(x)$ . However there is weak convergence. The quantity of material in each region does approach a limit, and the orientation can be defined. The limit can be described as a

composite material, achieved by homogenization of the original materials.

The mathematical theory is expressed by a relaxation of the original nonconvex problem. The problem is replaced by a well-posed (lower semicontinuous) problem which has the same minimum cost, but that minimum value is actually achieved (by a composite material). The solution of the relaxed problem is the weak limit of minimizing sequences in the original problem. Our joint work with Robert Kohn, referenced in the bibliography below, carried out an explicit relaxation and solution of problems in optimal design. It is comparatively straightforward in the case of scalar problems, but it becomes more complicated when the unknown  $u$  is a vector function. Elasticity and continuum mechanics produce the vector case, and much of our research was concentrated on the relaxation of functionals  $\int F(\text{grad } u) dx$ , in which  $\text{grad } u$  is the Jacobian matrix and quasiconvexity is the key property to achieve for  $F$ .

The long paper [1] summarizes our work on the interaction of homogenization, relaxation, and the mathematical theory of composite materials. In this report I will describe one specific problem solved separately in [4]. It was a central problem in Tartar's development of the method of compensated compactness, and it is an optimization problem for the effective properties of composites: How should conducting material be placed in a unit square so as to carry prescribed currents in the north-south and east-west directions, with a minimum area of material? We formulated this question as a nonconvex variational problem:

Minimize the area of the subset  $S \subset [0,1]^2$  subject to

$\iint |\nabla u|^2 dx dy = Q$ ,  $\iint |\nabla v|^2 dx dy = R$ ,  $\nabla u = \nabla v = 0$  outside  $S$ ,  
with boundary conditions  $u = 0$  on the left side,  $u = 1$  on the right,  $v = 0$  on the bottom, and  $v = 1$  on the top. The

stream functions are  $u$  and  $v$  (a vector unknown), the effective resistances of the square are  $Q$  and  $R$ , and the problem is to achieve those resistances with a minimum of material. The area  $(Q+R-2)/(QR-1)$  can be achieved by a suitable microstructure and the problem is to prove that this area is minimal.

The nonconvexity enters in the expression  $\iint_S dx dy$  for the area; the characteristic function equals one in  $S$  and zero in the complement. The difficulty is to compute the "quasiconvexification" of the functional  $F(\nabla u, \nabla v) = l_S + \lambda |\nabla u|^2 + \mu |\nabla v|^2$ , in which the Lagrange multipliers  $\lambda$  and  $\mu$  enter from the constraints. Kohn and I determined the largest function  $PF$  below  $F$  that is polyconvex (convex in  $\nabla u, \nabla v$ , and  $\det J$ ). We also established that this function is convex on lines connecting Jacobian matrices  $J = [\nabla u \quad \nabla v]$  that differ by rank one. Therefore  $PF$  is the correct quasiconvexification of  $F$ , and the relaxed problem requires the minimization of  $\iint PF(\nabla u, \nabla v) dx dy$ . That calculation led back to  $(Q+R-2)/(QR-1)$  as a lower bound on the area, and therefore the minimum.

Publications (Gilbert Strang)

I. Joint papers with Robert Kohn on optimal design

1. Optimal design and relaxation of variational problems, Communications on Pure and App. Math. 39 (1986) 113-137 (Part I), 139-182 (Part II), 353-377 (Part III).
2. Explicit relaxation of a variational problem in optimal design, Bull. Amer. Math. Soc. 9 (1983) 211-214.
3. The constrained least gradient problem, in Nonclassical Continuum Mechanics, R. Knops and A. Lacey, eds., Cambridge Univ. Press (1986).
4. The optimal design of a two-way conductor, in Nonsmooth Mechanics, P. D. Panagiotopoulos, J. J. Moreau, G. Strang, eds., Birkhäuser (1987).
5. Fibered structures in optimal design, Ordinary and Partial Differential Equations, Pitman Research Notes 157, B. Sleeman, ed. (1986).
6. Optimal design in elasticity and plasticity, Int. J. Numerical Meths. in Eng. 22 (1986) 183-188.

II. Expository papers on numerical and applied optimization

7. A framework for equilibrium equations, SIAM Review, 1988.
8. Karmarkar's algorithm in a nutshell, SIAM News 18 (1985) 13.
9. Karmarkar's algorithm and its place in applied mathematics, Math. Intelligencer 9 (1987) 4-10.

III. Papers on Toeplitz systems

10. A proposal for Toeplitz matrix calculations, Studies in Appl. Math. 74 (1986) 171-176.
11. The Toeplitz-circulant eigenvalue problem  $Ax = ACx$ , with A. Edelman, pp. 109-117 in Oakland Conf. on PDE's and Applied Mathematics, L. Bragg and J. Dettman, eds., Longmans (1987).

IV. Textbook on applied and engineering mathematics

12. Introduction to Applied Mathematics, Wellesley-Cambridge Press (1986).

Scientific Collaborators

Project DAAG29-83-K-0025

Professor Gilbert Strang

Principal Investigator: Massachusetts Institute of Technology  
Cambridge, MA 02139

Postdoctoral collaborator: Dr. Gao Yang

Predoctoral collaborators: Alan Edelman, Peiru Wu, Peter Zhuang

Ph.D. theses in progress

END

DATE

FILED

8-88

DTIC